# SPECIFICATIONS & TECHNICAL CHARACTERISTICS

DESCRIPTION	DETAILS
Body type	Hardtop
Body material	Steel (frame and bottom, hot dripped galvanized) and aluminum (cabin)
Steering	Skid steering
Tire size	1800x600x25 (72x23x25in)
Types of tyres	Tubeless, extra-low pressure
Suspension	Pneumatic circulating
Maximum speed (at the top-gear )	Up to 40 km/h (25 mph)
Minimum speed (at the low-gear)	2 km/h (1.2 mph)
Engine model	Hyundai Infracore (Formerly Doosan)
Fuel type	Diesel
Emission control	Stage 5 / Tier-4-final
Engine doc (Diesel Oxidation Catalyst )	DOC+DPF/DOC only
Fuel consumption	5 - 8 l/h
Engine displacement	1.8 L
Cylinder count	3

DESCRIPTION	DETAILS
Max engine power	41 kW (55 hp)
Max engine torque	190 nm
Generator performance	140 A
Fuel tank volume	95 L
Capacity of additional fuel canisters	4 x 58 L
Gearbox	Mechanical, 6-speed
Dry weight	2400 kg
Loading capacity	Up to 1200 kg
Towing capacity	2350 kg
Cabin internal volume	2 cu m
Rear space internal volume	5.8 cu m
Overall internal volume	7.8 cu m
Maintenance interval	250 hours (first 50 hours)
Parking brake system	Mechanical handbrake
Ground Clearance	550 mm





JSW Gecko Motors Private Limited 83, Industrial Area, Phase 1, Chandigarh, India-160002

Email: jsw.geckomotors@jsw.in Contact: +91 82839 99096 Follow us on Social Media









# SPECIALIST MOBILITY VEHICLE

SMV N1200 ATOR



The Ultimate
All Terrain Off Roader



# **SMV N1200 ATOR**

The SPECIALIST MOBILITY VEHICLE SMV N1200 ATOR is an amphibious all-terrain vehicle engineered to improve mobility, increase operational effectiveness, and guarantee safety across various environments. It delivers exceptional performance in difficult terrains, showcasing an impressive ability to overcome obstacles, transition smoothly from water to land, and break through ice.

# **WE REACH WHERE FEW DARE**

- Extreme Terrain
- Extreme Weather
- Extreme Mobility



# **Overall Dimension**


Height of Obstacles

4002 mm (157.6 in) Length

Climb

Descent

30°



Height without AC

2825.5mm (112.3 in)

Height

with AC

3028mm



2600 mm (102.36 in)

(119.2 in)

# **Service Tempreature**













- Rear seats 2 or 4 with seat belt
- Winch set
- Overhead locker (4)
- Set of cargo storage nets
- Side windows 4
- Interior cover suede leather
- Spare wheel kit (Tire 1800 mm, disc, badlock & bolt) (1 each in 1 set)


# **Hard top**

1200 Kg



Driver + up to 8 passengers





# **Base Model Includes:**

- Front cabin
- Rear compartment ROPS
- Rear view camera
- LED high & low beam
- Towing hitch integrated in front & rear bumpers
- Integrated front & rear door ladder
- Parking brake
- 2 Seats in front cabin with 3 Point seat belt (driver & co passenger)
- Glove boxes & cup holders
- Under floor storage boxes
- Additional fuel canister in each wheel
- ✓ A/C
- Preparation for winch set
- Foldable 7 rear seats with 3 point seat belt
- Side windows 2
- Side mirrors 2
- Autonomous heater
- Backup battery
- Interior fabric cover

- Front LED roof light bar
- Locker (2)
- Universal trailer
- Interior cover eco leather

# Max. Speed



# 40 Km/H

Dense forest, fallen trees, shaky ground, gravel, sand, peat bog, moor, marsh, dunes, rocks, swamps, baulders, scree, snow, ice

**GROUND** 



## 5 Km/H

Ponds, lakes, rivers, sandbanks, shelves, shores, coasts

WATER

# **Fuel Autonomy**



95-327 L from 5 lph

Main fuel tank of 95 litres and 4 supplementary fuel canisters of 58 litres each, provide vehicle fuel autonomy of more than 65 hours including non-stop running for 19 hours solely on the fuel from the main tank.